METHOD FOR TRANSMITTING ELECTRONIC DATA VIA TWO
DIFFERENT NETWORKS IN ORDER TO INCREASE INTERNET
SECURITY

5   The present invention relates to a method, based on
        patent claim 1, which drastically reduces the known
        rates of hacker attacks on computer systems today.
        There are numerous devices for the security of computer
        systems, but they do not fulfill their purpose. They
10   require vast amounts of resources, and despite this
        computer hackers cause 600 – 800 billion USD (American
        dollars) of damage annually worldwide.

        The central element in communication among computer
15   systems is the packet. The data are split serially into
        packets. This means that the first X bits are defined
        as packet 1, the second X bits are defined as packet 2
        etc. These packets are then sent from the sender to the
        receiver in a network (e.g. on the internet). Apart
20   from data, the packets contain addresses and rules
        regarding how they need to be assembled again at the
        receiver. Even if partial encryption is used,
        everything can be found at the same location, at the
        same time (in the same time window), in one packet and
25   in the same network. For this very reason, the data in
        such packets in a network are susceptible to
        unauthorized access. These facts are actually what make
        it possible for hackers to "tap" lines and read
        confidential data or penetrate other computer systems.
30   "Lines" are also to be understood to mean wireless
        communication channels.
        All the security devices used (encryption, various
        algorithms, signature, firewall, virtual networks,
        Secure Sockets Layer) change nothing about the facts
35   presented above, however, and are therefore also not
        able to take satisfactory care of the security of the
        computer systems involved.

- 2 -

It is the object of the invention to eliminate these drawbacks. This object is achieved by the features of patent claim 1.

5   The physical (geographical) and spectral separation of the data during the time-shifted transmission in two networks give unauthorized access to the actual data next to no chance.

10   The quintessence of the method is the physical (geographical) and spectral separation of the data and a small time shift in the transmission in two networks (dual network), figure 1, so that the separate data are already implicitly encrypted – by a new method of
15   packet preprocessing, table 1.

Bit number	0	1	2	3	4	5	6	7	8	9	10	N	Packet length*
Packet today	1	1	0	0	1	0	0	1	1	1	0	...	4096
O packet*		1		0		0		1		1		...	2048
E packet*	1		0		1		0		1		0	...	2048

*) O packet = odd bits, E packet = even bits, N = number, packet lengths are examples

20   **Table 1**

This new method of preprocessing the data into O packets and into E packets produces two, independently useless halves of the information which hackers are no
25   longer able to evaluate. The implicit encryption also results in a saving on bandwidth or an increase in throughput.

The example involves 2048 bits/packet/network (O

network and E network), as shown in table 1. This is a long way over the critical length per O packet and per E packet. Today's computers cannot calculate this length for the packets - within a useful period - through combination ("trying out" all options, by means of a computer program.)

Addresses, message identification (message ID) and the packet numbering, which are likewise part of a packet, are not changed by this method.

An exemplary embodiment will be used to explain the invention with reference to a figure (figure 1). Figure 1 shows an embodiment of the inventive dual network, with a sender and with a receiver, and also with the path taken in the O network (dashed lines) by an O packet (dashed arrows) and with the path taken in the E network (solid lines) by an E packet (solid arrows).

A sender 1 sends a message to a receiver 8. The message comprises O packets 4u and E packets 4g.

An O packet 4u in the O network 5u takes the following path:
O port 2u on the sender 1,
O provider 3u for the sender 1,
O network 5u,
O provider 6u for the receiver 8,
O port 7u on the receiver 8.

An E packet 4g in the E network 5g takes the following path:
E port 2g on the sender 1,
E provider 3g for the sender 1,
E network 5g,
E provider 6g for the receiver 8,
E port 7g on the receiver 8.

When the O packets 4u and the E packets 4g have been preprocessed, the data are transmitted from the sender to the receiver. The O packets via the O network 5u, and the E packets via the E network 5g. These are two, clearly separate networks (dual network), without a common node. The networks are produced through quasi-duplication of today's networks, which we are calling O network and E network (O = odd, E = even). Duplication is to be understood to mean duplication of the number of nodes - in today's network. This is merely quasi-duplication, because the number of O nodes and the number of E nodes do not need to be identical. (The number of routers or gateways in the O network and in the E network do not have to be identical.) The nodes in the two networks are at different locations.

The available spectrum (bandwidth) is used dynamically. This dynamic allocation of the channels, the distance between the nodes in the two networks and the dynamic routing produce the physical (geographical) and spectral separation of the O packets and the E packets during transmission.

Each terminal (PC, server) has two identities: O identity and E identity. One connects the terminal to the O network and the other connects it to the E network. The O packets look for their path in the O network, and the E packets look for their path in the E network. This is done without any indication that they belong together and that they will arrive at the same terminal.

Devices which are responsible for forwarding the packets in the respective network (routers and gateways) are respectively connected just to one network (O network or E network) and perform their tasks as though there were just one network. This is

normal practice today - before the introduction of the
dual network.

After the transmission, the receiver reassembles the O
5 packets and the E packets.

A transmission usually comprises more than just one
packet. One component of the packets is an
identification of the transmission (message ID). In the
10 dual network there is one for the O network and one for
the E network. At the end of the transmission - as the
last O packet - the sender sends the E message
identification (E message ID) for the transmission in
the E network (or vice versa) to the receiver. This
15 allows the (authorized) receiver to reassemble the O
packets and the E packets.

In theory, the dual network can be generalized as an N
network (N = 1, 2, 3, ...).
20
The dual network proposed here is suitable for any
transmission medium. It is undoubtedly simpler to
connect the terminals to the two networks for the
wireless communication.
25
Conventional certification, signature and cryptography
can be used in combination with the dual network.